



PORTABLE SHUNT RESISTOR



Serie "Classic"

The measuring ranges of ammeter HDA and PDA can be extended by the shunt SH

This shunt is made in two different constructions:

1. with 4 measuring ranges installed into a plastic case with pressure bolt terminal.
2. with 1 measuring range in self-carrying construction with screw terminal.

Technical data

Class of accuracy: 0,2 according to VDE 0410.

Voltage drop: 60 mV.

Weight: 0,3-1,8 kg.

Dimensions: 202x110x97 mm 6-12-30-60 A
 202x110x97 mm 12-30-60-120 A
 215x55x30 mm 300 A and 600 A
 230x110x65 mm 1200 A



TYPE	Cat. No.	Class of acc.	Measuring ranges	Voltage drop	Dimensions	Mass	Remark
SH	0891-90-001	0.2	6-12-30-60A	60 mV	202x110x97 mm	approx. 1.6 kg	in plastic case
	0891-90-000		12-30-60-120 A	60 mV	202x110x97 mm	approx. 1.6 kg	
	0831-90-000		300 A	60 mV	215x55x50 mm	approx. 0.8 kg	self-carrying layout
	0830-90-000		600 A	60 mV	215x55x50 mm	approx. 2.0 kg	
	0829-90-000		1200 A	60 mV	230x110x65 mm	approx. 2.9 kg	

Order specification:

- Portable shunt resistor.
- Range: 600 A