








Voltages:		24V, 48V, 60V, 110V, 120V, 230V, 240V, 400V (±10%)
Frequency:		50 Hz, 60 Hz
Counting range:	AC	99999.99 hours
Number of digits:		5 integers, 2 decimals
Operating temperature:		-25°C....+80°C
Voltages:		6 - 30V, 10 - 80V, 110V (±10%)
Counting range:		999999.9 hours
Number of digits:	DC	6 integers, 1 decimals
Operating temperature:		-20°C....+70°C
Protection:		IP 40 - front side IP 20 - terminals
Front dimensions:		48x48 mm
Adapter frames:		52x52, 55x55, 72x72, ∅ 80 mm
Special protection:		IP 65 - front side IP 20 - terminals
Approval:		CE mark , UL recognized, CSA certified
Connection:		plug 6.3 x 0.8 mm with screw plug 6.3 x 0.8 mm screw terminals

MOUNTING	TYPE	HK 46 CUTOUT	
aluminium clamp	A		45x45 mm chamfer edge ∅51 mm, □45 mm
retainer	G		45x45 mm chamfer edge ∅51 mm, □45 mm
DIN rail	D		
snap fastener	F		45x45 mm chamfer edge
anti-vibration rubber ∅80 mm	C		∅71 mm
3-screw front mounting ∅72 mm	H		