

hour meters



|                        |    |  |
|------------------------|----|--|
| Voltages:              |    | 24V, 48V, 60V, 110V, 120V, 230V,<br>240V, 400V ( ±10%)               |
| Frequency:             |    | 50 Hz, 60 Hz   |
| Counting range:        | AC | 99999.99 hours   |
| Number of digits:      |    | 5 integers, 2 decimals   |
| Operating temperature: |    | -25°C....+80°C   |
| Voltages:              |    | 6 - 30V, 10 - 80V, 110V (±10%)                                       |
| Counting range:        | DC | 999999.9 hours   |
| Number of digits:      |    | 6 integers, 1 decimals   |
| Operating temperature: |    | -20°C....+70°C   |
| Protection:            |    | IP 65 - front side<br>IP 00 - terminals                              |
| Front dimensions:      |    | ∅58 mm   |
| Adapter frames:        |    | ∅72 and ∅80 mm   |
| Special protection:    |    | IP 67 - front side<br>IP 00 - terminals                              |
| Approval:              |    | CE mark , UL recognized, CSA certified                               |
| Connection:            |    | plug 6.3 x 0.8 mm with screw<br>plug 6.3 x 0.8 mm<br>screw terminals |

| MOUNTING                      | TYPE |  | HK 47 CUTOUT |
|-------------------------------|------|--|--------------|
| aluminium clamp               | A    |  | ∅50 mm       |
| retainer                      | G    |  |              |
| DIN rail                      | D    |  |              |
| snap fastener                 | F    |  |              |
| anti-vibration rubber ∅80 mm  | C    |  | ∅71 mm       |
| 3-screw front mounting ∅72 mm | H    |  | ∅58 mm       |